


Quartz Crystal Series

1008B

Features

- ◆RoHS Compliant
- ◆Ceramic/metal package



Electrical Specifications

Item	Specifications	Remarks
Nominal Frequency Range	40.000MHz to 120.000MHz	Fund.; AT-Cut
Frequency Tolerance	±10ppm(Standard) at 25°C±3°C	Others are offered
Load Capacitance	Fund.:6pF to 12pF	Please specify
Series Resistance	As ESR table	
Shunt Capacitance	1.0pF Max	
Drive Level	200μW Max	10μW(Standard)
Operating Temperature	-20°C to +70°C(Standard)	Others are offered
Storage Temperature	-55°C to +125°C	
Stability vs. Temperature	±20ppm(Standard)	Others are offered
Insulated Resistance	500MΩ	Minimum
Aging	±1ppm/year	Maximum

ESR(Series Resistance)

Frequency(MHz)	Mode	Ohm Max	Frequency(MHz)	Mode	Ohm Max
40.000~52.000	Fund.;AT	100	96.001~120.000	AT	40
52.001~96.000	Fund.;AT	60			

Stability vs. Temperature

◆ Standard		1	2	3	5	6	7	Remarks
◇ Please specify		±10ppm	±20ppm	±30ppm	±50ppm	±15ppm	±25ppm	
B	-10°C to +60°C	◇				◇		
C	-20°C to +70°C	◇	◆	◇	◇	◇	◇	Standard
D	-40°C to +85°C		◇	◇	◆	◇	◇	

Ordering Information

Q	R	Type	Pin	XX.XXXX	M	Mode	CL pF	Freq.Tolerance at 25°C	Operating Temp.	Stability Vs.Temp.	Option
---	---	------	-----	---------	---	------	-------	------------------------	-----------------	--------------------	--------

Q:Quartz 08: 1.0*0.8mm B:4 Center frequency 40.0 to 120.0MHz M: MHz F:Fund.;AT See Table ±10ppm to ±50ppm See Table See Table F:Lead Free Blank:T&R

Example:QR08B40.0000MFF1C2F (Crystal,SMD1.0*0.8mm,40.0000MHz,4pins,8pF,+/-10ppm,-20 to +70deg,+/-20ppm.T&R,Lead free)


Load Capacitance Codes

6pF:	D	7pF:	E	8pF:	F	9pF:	B
10pF:	R	12pF:	T				

Quartz Crystal Series

1008B

Dimensions



Unit:mm

Reflow Soldering Profile

